

PrevaLED COIN 111 COB G2

LED modules with integrated optics and heat sink



Product family features

- Color consistency < 2 SDCM
- TM30 compliant
- High flux output up to 4900 lm
- Beam angle: 15°, 24°, 40°, 60°
- Type of protection: IP20

Product family benefits

- Compact form factor compatible with conventional AR111 lamps
- Precise optical control and free from multi-shadow issue
- Dual mode options in High-Output (HO) and High-Efficacy (HE)

Areas of application

- Retail, shop, restaurant, hospitality
- High-end residential
- Suitable for indoor applications
- Connecting multiple modules in parallel on one LED driver is not permitted
- Connecting multiple modules in series on one LED driver is not recommended
- Do not use in sealed fixtures
- Avoid covering the lens with dust or any object



Product family datasheet

Technical data

Product description	Electrical data					Photometrical data
	Nominal current	Nominal voltage	Type of current	Energy consumption in on-mode	On-mode power	Luminous efficacy
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.5 kWh/1000h ²⁾	25.50 W	118 lm/W
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.5 kWh/1000h ²⁾	25.50 W	115 lm/W
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.5 kWh/1000h ²⁾	25.50 W	112 lm/W
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	125 lm/W
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	122 lm/W
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	119 lm/W
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	123 lm/W
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.6 kWh/1000h ²⁾	25.60 W	120 lm/W
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.5 kWh/1000h ²⁾	25.50 W	118 lm/W
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	96 lm/W
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	94 lm/W
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.1 kWh/1000h ²⁾	25.10 W	91 lm/W
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.7 kWh/1000h ²⁾	25.70 W	101 lm/W
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.5 kWh/1000h ²⁾	25.50 W	98 lm/W
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.3 kWh/1000h ²⁾	25.30 W	96 lm/W
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.6 kWh/1000h ²⁾	25.60 W	93 lm/W
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	89 lm/W
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	104 lm/W
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.3 kWh/1000h ²⁾	25.30 W	101 lm/W
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.2 kWh/1000h ²⁾	25.20 W	99 lm/W
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	0.7 A	36.2 V	DC	25.6 kWh/1000h ²⁾	25.60 W	106 lm/W
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	0.7 A	36.2 V	DC	25.5 kWh/1000h ²⁾	25.50 W	104 lm/W
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	0.7 A	36.2 V	DC	25.4 kWh/1000h ²⁾	25.40 W	101 lm/W
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	1.05 A	35.0 V	DC	36.6 kWh/1000h ²⁾	36.60 W	127 lm/W

Product family datasheet

Product description	Electrical data					Photometrical data
	Nominal current	Nominal voltage	Type of current	Energy consumption in on-mode	On-mode power	Luminous efficacy
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	1.05 A	35.0 V	DC	36.9 kWh/1000h ²⁾	36.90 W	124 lm/W
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	1.05 A	35.0 V	DC	36.9 kWh/1000h ²⁾	36.90 W	122 lm/W
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	1.05 A	35.0 V	DC	36.8 kWh/1000h ²⁾	36.80 W	134 lm/W
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	1.05 A	35.0 V	DC	37.1 kWh/1000h ²⁾	37.10 W	131 lm/W
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	1.05 A	35.0 V	DC	37.2 kWh/1000h ²⁾	37.20 W	129 lm/W
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	1.05 A	35.0 V	DC	36.7 kWh/1000h ²⁾	36.70 W	132 lm/W
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	1.05 A	35.0 V	DC	37.1 kWh/1000h ²⁾	37.10 W	129 lm/W
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	1.05 A	35.0 V	DC	36.7 kWh/1000h ²⁾	36.70 W	127 lm/W
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	1.05 A	35.0 V	DC	36.9 kWh/1000h ²⁾	36.90 W	103 lm/W
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	1.05 A	35.0 V	DC	36.8 kWh/1000h ²⁾	36.80 W	100 lm/W
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	1.05 A	35.0 V	DC	36.9 kWh/1000h ²⁾	36.90 W	99 lm/W
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	1.05 A	35.0 V	DC	36.9 kWh/1000h ²⁾	36.90 W	108 lm/W
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	1.05 A	35.0 V	DC	36.7 kWh/1000h ²⁾	36.70 W	106 lm/W
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	1.05 A	35.0 V	DC	36.8 kWh/1000h ²⁾	36.80 W	104 lm/W
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	1.05 A	35.0 V	DC	36.6 kWh/1000h ²⁾	36.60 W	112 lm/W
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	1.05 A	35.0 V	DC	36.8 kWh/1000h ²⁾	36.80 W	109 lm/W
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	1.05 A	35.0 V	DC	36.9 kWh/1000h ²⁾	36.90 W	108 lm/W
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	1.05 A	35.0 V	DC	37.7 kWh/1000h ²⁾	37.70 W	114 lm/W
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	1.05 A	35.0 V	DC	36.7 kWh/1000h ²⁾	36.70 W	111 lm/W
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	1.05 A	35.0 V	DC	36.8 kWh/1000h ²⁾	36.80 W	110 lm/W

Product description	Light color (designation)	Colour consistency (McAdam ellipses)	Peak luminous intensity	Useful luminous flux (Φ _{use})	Color rendering index Ra
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	3000 K	2	22589	2800 lm ³⁾	80

Product family datasheet

Product description	Light color (designation)	Colour consistency (McAdam ellipses)	Peak luminous intensity	Useful luminous flux (Φuse)	Color render- ing index Ra
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	3000 K	2	13300	2700 lm ³⁾	80
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	3000 K	2	6145	2560 lm ³⁾	80
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	4000 K	2	23876	2900 lm ³⁾	80
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	4000 K	2	14419	2800 lm ³⁾	80
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	4000 K	2	6495	2650 lm ³⁾	80
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	6500 K	2	23618	2800 lm ³⁾	80
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	6500 K	2	14265	2700 lm ³⁾	80
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	6500 K	2	6426	2650 lm ³⁾	80
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	2700 K	2	18335	2200 lm ³⁾	90
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	2700 K	2	11073	2100 lm ³⁾	90
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	2700 K	2	4990	2050 lm ³⁾	90
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	3000 K	2	19288	2350 lm ³⁾	90
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	3000 K	2	11649	2250 lm ³⁾	90
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	3000 K	2	5247	2150 lm ³⁾	90
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	3000 K	2	17895	2350 lm ³⁾	90
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	3000 K	2	4869	2160 lm ³⁾	90
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	3500 K	2	19879	2450 lm ³⁾	90
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	3500 K	2	12004	2300 lm ³⁾	90
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	3500 K	2	5409	2200 lm ³⁾	90
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	4000 K	2	20295	2500 lm ³⁾	90
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	4000 K	2	12257	2400 lm ³⁾	90
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	4000 K	2	5523	2300 lm ³⁾	90
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	3000 K	2	13904	4150 lm ³⁾	80
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	3000 K	2	8401	4000 lm ³⁾	80
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	3000 K	2	4845	3700 lm ³⁾	80
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	4000 K	2	14699	4350 lm ³⁾	80
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	4000 K	2	8880	4090 lm ³⁾	80
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	4000 K	2	5122	3900 lm ³⁾	80
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	6500 K	2	14472	4350 lm ³⁾	80
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	6500 K	2	8743	4050 lm ³⁾	80
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	6500 K	2	5043	3850 lm ³⁾	80
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	2700 K	2	11281	3400 lm ³⁾	90
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	2700 K	2	6815	3200 lm ³⁾	90
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	2700 K	2	3931	3000 lm ³⁾	90
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	3000 K	2	11867	3450 lm ³⁾	90
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	3000 K	2	7169	3350 lm ³⁾	90
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	3000 K	2	4135	3150 lm ³⁾	90
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	3500 K	2	12241	3600 lm ³⁾	90
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	3500 K	2	7396	3400 lm ³⁾	90
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	3500 K	2	4265	3300 lm ³⁾	90
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	4000 K	2	12507	3800 lm ³⁾	90

Product family datasheet

Product description	Light color (designation)	Colour consistency (McAdam ellipses)	Peak luminous intensity	Useful luminous flux (Φ _{use})	Color rendering index Ra
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	4000 K	2	7557	3550 lm ³⁾	90
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	4000 K	2	4358	3450 lm ³⁾	90

Product description	Correlated color temperature CCT	Light technical data			Dimensions & weight
		Starting time	Warm-up time (60 %)	Beam angle	Diameter
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	6300 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	6300 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	6300 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	2700 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	2700 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	2700 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	3100 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	3100 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	3400 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	3400 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	3400 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	15 °	110.0 mm ⁴⁾
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	20 °	110.0 mm ⁴⁾

Product family datasheet

Product description	Correlated color temperature CCT	Light technical data			Dimensions & weight
		Starting time	Warm-up time (60 %)	Beam angle	Diameter
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	35 °	110.0 mm ₄₎
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	6300 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	6300 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	6300 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	2700 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	2700 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	2700 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	3000 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	3400 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	3400 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	3400 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	24 °	110.0 mm ₄₎
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	37 °	110.0 mm ₄₎
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	3900 K	< 0.5 s	< 2.00 s	55 °	110.0 mm ₄₎

Product description	Product weight	Width	Length	Height
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm

Product family datasheet

Product description	Product weight	Width	Length	Height
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	385.00 g	110.0 mm	110.0 mm	52.0 mm

Product family datasheet

Product description	Colors & materials	Temperatures & operating conditions		
	Heatsink color	Performance temp. acc. to IEC 62717	Maximum temperature at tc test point	Ambient temperature range
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	Grey	65 °C	90 °C	-25...+40 °C
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	Grey	75 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	Grey	75 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	Grey	75 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C

Product family datasheet

Product description	Colors & materials	Temperatures & operating conditions		
	Heatsink color	Performance temp. acc. to IEC 62717	Maximum temperature at tc test point	Ambient temperature range
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	Grey	80 °C	100 °C	-25...+40 °C

Product description	Temperature range at storage	Lifespan		
		Number of switching cycles	L70B50 lifetime	Lumen maintenance factor LMF
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	-40...80 °C	15000	50000 h	96 ²⁾
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	-40...80 °C	15000	50000 h	96 ²⁾
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	-40...80 °C	15000	50000 h	96 ²⁾
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	-40...80 °C	15000	50000 h	96 ²⁾
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾

Product family datasheet

Product description	Temperature range at storage	Lifespan		
		Number of switching cycles	L70B50 lifetime	Lumen maintenance factor LMF
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	-40...80 °C	15000	50000 h ²⁾	96 ²⁾

Product description	Additional product data	Capabilities	Certificates & standards	
	Lighting technology used	Dimmable	Standards	Energy efficiency class
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E

Product family datasheet

	Additional product data	Capabilities	Certificates & standards	
Product description	Lighting technology used	Dimmable	Standards	Energy efficiency class
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F

Product family datasheet

	Additional product data	Capabilities	Certificates & standards	
Product description	Lighting technology used	Dimmable	Standards	Energy efficiency class
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F

Product family datasheet

	Additional product data	Capabilities	Certificates & standards	
Product description	Lighting technology used	Dimmable	Standards	Energy efficiency class
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E

Product family datasheet

	Additional product data	Capabilities	Certificates & standards	
Product description	Lighting technology used	Dimmable	Standards	Energy efficiency class
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F

Product family datasheet

	Additional product data	Capabilities	Certificates & standards	
Product description	Lighting technology used	Dimmable	Standards	Energy efficiency class
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	E
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	LED	Yes	Acc. to IEC 62471/Acc. to EN 60598-1/Acc. to EN 60529/Acc. to EN 55015/Acc. to EN 61547/Acc. To EN62031 IEC 605981/CE	F

	Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Commodity code	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621664	No declarable substances contained
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621756	No declarable substances contained
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	85395100000	18-04-2022	4052899620995	No declarable substances contained
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621671	No declarable substances contained

Product family datasheet

	Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Commodity code	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621763	No declarable substances contained
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621008	No declarable substances contained
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621688	No declarable substances contained
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621770	No declarable substances contained
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621015	No declarable substances contained
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621695	No declarable substances contained
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621787	No declarable substances contained
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621022	No declarable substances contained
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621701	No declarable substances contained
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621794	No declarable substances contained
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621039	No declarable substances contained
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	85395100000	30-06-2023	4052899621732	No declarable substances contained
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	85395100000	30-06-2023	4052899621060	No declarable substances contained
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621718	No declarable substances contained
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621800	No declarable substances contained
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621046	No declarable substances contained
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	85395100000	18-04-2022	4052899621725	No declarable substances contained
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621817	No declarable substances contained
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621053	No declarable substances contained
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621398	No declarable substances contained
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621480	No declarable substances contained
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621572	No declarable substances contained
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621404	No declarable substances contained
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621497	No declarable substances contained

Product family datasheet

	Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Commodity code	Date of Declaration	Primary Article Identifier	Candidate List Substance 1
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621589	No declarable substances contained
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621411	No declarable substances contained
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621503	No declarable substances contained
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621596	No declarable substances contained
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621428	No declarable substances contained
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621510	No declarable substances contained
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621602	No declarable substances contained
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621435	No declarable substances contained
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621527	No declarable substances contained
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621619	No declarable substances contained
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621442	No declarable substances contained
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621534	No declarable substances contained
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621626	No declarable substances contained
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	85395100000	18-04-2022	4052899621459	No declarable substances contained
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	85395100000	18-04-2022	4052899621541	No declarable substances contained
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	85395100000	18-04-2022	4052899621633	No declarable substances contained

Product description	Declaration No. in SCIP database
PL-CN111-COB- 2800-830-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-830-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-830-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-840-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-840-24D-G2 ¹⁾	No declarable substances contained

Product family datasheet

Product description	Declaration No. in SCIP database
PL-CN111-COB- 2800-840-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-865-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-865-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-865-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-927-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-927-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-927-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-930-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-930-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-930-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-930UW-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-930UW-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-935-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-935-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-935-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-940-15D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-940-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 2800-940-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-830-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-830-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-830-60D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-840-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-840-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-840-60D-G2 ¹⁾	No declarable substances contained

Product family datasheet

Product description	Declaration No. in SCIP database
PL-CN111-COB- 4300-865-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-865-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-865-60D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-927-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-927-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-927-60D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-930-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-930-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-930-60D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-935-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-935-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-935-60D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-940-24D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-940-40D-G2 ¹⁾	No declarable substances contained
PL-CN111-COB- 4300-940-60D-G2 ¹⁾	No declarable substances contained


¹⁾ Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information (see www.osram.com/led-systems),/All the technical parameters apply to the entire module. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values/Tolerance for optical and electrical data: +/-10%

²⁾ _


³⁾ 90°

⁴⁾ ±0.5 mm


Product family datasheet



CN111 COB G2



CN111 COB G2



PL CN111 COB G2 DRAW 051021

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Download Data

File	
	Certificates PL CN111 COB G2 ENEC 181121
	Declarations of conformity PL CN111 COB CE 4276330 160623

Product family datasheet

	CAD data PL CN111 COB G2 STEP 160321
	CAD data PL CN111 G2 STEP 041121
	IES data PL CN111 COB 2800 830 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 830 24D G2.1 IES 250321
	IES data PL CN111 COB 2800 830 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 840 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 840 24D G2.1 IES 250321
	IES data PL CN111 COB 2800 840 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 865 15D G2.1 IES 250321
	Product line drawing - technical CN111 COB G2
	CAD Data 2-dim CN111 COB G2
	IES data PL CN111 COB 2800 865 24D G2.1 IES 250321
	IES data PL CN111 COB 2800 865 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 927 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 927 24D G2.1 IES 250321
	IES data PL CN111 COB 2800 927 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 930 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 930 24D G2.1 IES 250321
	IES data PL CN111 COB 2800 930 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 930UW 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 930UW 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 935 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 935 24D G2.1 IES 250321

Product family datasheet

	IES data PL CN111 COB 2800 935 40D G2.1 IES 250321
	IES data PL CN111 COB 2800 940 15D G2.1 IES 250321
	IES data PL CN111 COB 2800 940 24D G2.1 IES 250321
	IES data PL CN111 COB 2800 940 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 830 24D G2.1 IES 250321
	IES data PL CN111 COB 4300 830 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 830 60D G2.1 IES 250321
	IES data PL CN111 COB 4300 840 24D G2.1 IES 250321
	IES data PL CN111 COB 4300 840 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 840 60D G2.1 IES 250321
	IES data PL CN111 COB 4300 865 24D G2.1 IES 250321
	IES data PL CN111 COB 4300 865 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 865 60D G2.1 IES 250321
	IES data PL CN111 COB 4300 927 24D G2.1 IES 250321
	IES data PL CN111 COB 4300 927 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 927 60D G2.1 IES 250321
	IES data PL CN111 COB 4300 930 24D G2.1 IES 250321
	IES data PL CN111 COB 4300 930 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 930 60D G2.1 IES 250321
	IES data PL CN111 COB 4300 935 24D G2.1 IES 250321
	IES data PL CN111 COB 4300 935 40D G2.1 IES 250321
	IES data PL CN111 COB 4300 935 60D G2.1 IES 250321
	IES data PL CN111 COB 4300 940 24D G2.1 IES 250321

Product family datasheet



IES data
PL CN111 COB 4300 940 40D G2.1 IES 250321



IES data
PL CN111 COB 4300 940 60D G2.1 IES 250321

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899621664	PL-CN111-COB- 2800-830-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621756	PL-CN111-COB- 2800-830-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899620995	PL-CN111-COB- 2800-830-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621671	PL-CN111-COB- 2800-840-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621763	PL-CN111-COB- 2800-840-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621008	PL-CN111-COB- 2800-840-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621688	PL-CN111-COB- 2800-865-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621770	PL-CN111-COB- 2800-865-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621015	PL-CN111-COB- 2800-865-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621695	PL-CN111-COB- 2800-927-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621787	PL-CN111-COB- 2800-927-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621022	PL-CN111-COB- 2800-927-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621701	PL-CN111-COB- 2800-930-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g

Product family datasheet

Logistical Data

4052899621794	PL-CN111-COB- 2800-930-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621039	PL-CN111-COB- 2800-930-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621732	PL-CN111-COB- 2800-930UW-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621060	PL-CN111-COB- 2800-930UW-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621718	PL-CN111-COB- 2800-935-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621800	PL-CN111-COB- 2800-935-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621046	PL-CN111-COB- 2800-935-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621725	PL-CN111-COB- 2800-940-15D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621817	PL-CN111-COB- 2800-940-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621053	PL-CN111-COB- 2800-940-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621398	PL-CN111-COB- 4300-830-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621480	PL-CN111-COB- 4300-830-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621572	PL-CN111-COB- 4300-830-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621404	PL-CN111-COB- 4300-840-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621497	PL-CN111-COB- 4300-840-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621589	PL-CN111-COB- 4300-840-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621411	PL-CN111-COB- 4300-865-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621503	PL-CN111-COB- 4300-865-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621596	PL-CN111-COB- 4300-865-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621428	PL-CN111-COB- 4300-927-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621510	PL-CN111-COB- 4300-927-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g

Product family datasheet

Logistical Data

4052899621602	PL-CN111-COB- 4300-927-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621435	PL-CN111-COB- 4300-930-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621527	PL-CN111-COB- 4300-930-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621619	PL-CN111-COB- 4300-930-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621442	PL-CN111-COB- 4300-935-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621534	PL-CN111-COB- 4300-935-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621626	PL-CN111-COB- 4300-935-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621459	PL-CN111-COB- 4300-940-24D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621541	PL-CN111-COB- 4300-940-40D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g
4052899621633	PL-CN111-COB- 4300-940-60D-G2	Shipping carton box 12	280 mm x 254 mm x 209 mm	14.86 dm ³	5443.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
PL-CN111-COB- 2800-830-15D-G2	24D LENS FOR COIN 111 COB G2	4062172235099
PL-CN111-COB- 2800-830-15D-G2	40D LENS FOR COIN 111 COB G2	4062172235112
PL-CN111-COB- 2800-830-15D-G2	BLACK COVER FOR COIN 111 COB G2	4062172251822
PL-CN111-COB- 2800-830-15D-G2	PL-CN111 -ROUND-RING	4052899306820
PL-CN111-COB- 2800-830-24D-G2	15D LENS FOR COIN 111 COB G2	4062172235075
PL-CN111-COB- 2800-830-24D-G2	40D LENS FOR COIN 111 COB G2	4062172235112
PL-CN111-COB- 2800-830-24D-G2	BLACK COVER FOR COIN 111 COB G2	4062172251822
PL-CN111-COB- 2800-830-24D-G2	PL-CN111 -ROUND-RING	4052899306820

Product family datasheet

PL-CN111-COB- 2800-830-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-830-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-830-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-830-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-840-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-840-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-840-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-840-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-840-24D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-840-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-840-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-840-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-840-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-840-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-840-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-840-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-865-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-865-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-865-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-865-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-865-24D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-865-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-865-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822

Product family datasheet

PL-CN111-COB- 2800-865-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-865-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-865-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-865-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-865-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-927-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-927-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-927-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-927-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-927-24D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-927-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-927-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-927-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-927-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-927-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-927-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-927-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-930-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-930-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-930-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-930-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-930-24D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-930-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112

Product family datasheet

PL-CN111-COB- 2800-930-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-930-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-930-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-930-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-930-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-930-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-930UW-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-930UW-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-930UW-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-930UW-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-930UW-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-930UW-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-930UW-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-930UW-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-935-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-935-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-935-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-935-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-935-24D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-935-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-935-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-935-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-935-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075

Product family datasheet

PL-CN111-COB- 2800-935-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-935-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-935-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-940-15D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-940-15D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-940-15D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-940-15D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-940-24D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-940-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 2800-940-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-940-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 2800-940-40D-G2	15D LENS FOR COIN 111 COB G2	▶	4062172235075
PL-CN111-COB- 2800-940-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 2800-940-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 2800-940-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-830-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-830-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-830-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-830-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-830-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-830-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-830-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-830-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820

Product family datasheet

PL-CN111-COB- 4300-830-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-830-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-830-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-830-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-840-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-840-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-840-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-840-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-840-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-840-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-840-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-840-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-840-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-840-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-840-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-840-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-865-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-865-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-865-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-865-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-865-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-865-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-865-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822

Product family datasheet

PL-CN111-COB- 4300-865-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-865-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-865-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-865-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-865-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-927-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-927-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-927-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-927-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-927-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-927-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-927-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-927-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-927-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-927-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-927-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-927-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-930-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-930-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-930-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-930-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-930-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-930-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099

Product family datasheet

PL-CN111-COB- 4300-930-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-930-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-930-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-930-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-930-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-930-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-935-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-935-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-935-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-935-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-935-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-935-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-935-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-935-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-935-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-935-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-935-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-935-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-940-24D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150
PL-CN111-COB- 4300-940-24D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-940-24D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-940-24D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-940-40D-G2	60D LENS FOR COIN 111 COB G2	▶	4062172235150

Product family datasheet

PL-CN111-COB- 4300-940-40D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-940-40D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-940-40D-G2	PL-CN111 -ROUND-RING	▶	4052899306820
PL-CN111-COB- 4300-940-60D-G2	24D LENS FOR COIN 111 COB G2	▶	4062172235099
PL-CN111-COB- 4300-940-60D-G2	40D LENS FOR COIN 111 COB G2	▶	4062172235112
PL-CN111-COB- 4300-940-60D-G2	BLACK COVER FOR COIN 111 COB G2	▶	4062172251822
PL-CN111-COB- 4300-940-60D-G2	PL-CN111 -ROUND-RING	▶	4052899306820

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.