



LED REFLECTOR LAMPS UTTERLY IMPRESSIVE

ด้วยประสิทธิภาพที่เข้ากันได้ กำลังวัตต์ และขนาดที่ใกล้เคียงกับหลอดฮาโลเจนทั่วไป ในขณะที่ให้อัตราส่วนราคาต่อประสิทธิภาพที่โดดเด่น คุณภาพแสง และเทคโนโลยีแสงธรรมชาติล่าสุด หลอดไฟสะท้อนแสง LED OSRAM ที่หลากหลายจาก LEDVANCE มีโซลูชันที่สมบูรณ์แบบสำหรับทุกความต้องการใช้งาน

คุณสมบัติ

สูงสุด CRI>97 การแสดงผลสี
อายุการใช้งานสูงสุด 40,000 ชั่วโมง
ให้การกระจายแสงเป็นเนื้อเดียวกัน



LED VALUE HV MR16 50

LED ECO HV MR16 50

High-voltage LED reflector lamps MR16 with retrofit pin base



CRI
80

LED VALUE HV MR16 50

Product Name	GTIN (EAN)														
LV MR16 36 7.5W/827 100-240V GU5.3	4058075229648	50	GU5.3	7.5	700	1,200	2,700	80	—	36°	50	50	15,000	10	1
LV MR16 36 7.5W/830 100-240V GU5.3	4058075719200	50	GU5.3	7.5	700	1,200	3,000	80	—	36°	50	50	15,000	10	1

LED ECO HV MR16 50

Product Name	GTIN (EAN)														
LE MR16 36 5.5W/827 230V GU5.3	4058075430594	50	GU5.3	5.5	500	880	2,700	80	—	36°	45	50	15,000	10	2
LE MR16 36 5.5W/865 230V GU5.3	4058075430617	50	GU5.3	5.5	525	930	6,500	80	—	36°	45	50	15,000	10	2

* Lamp + socket

¹ All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters of each individual product, which can deviate from the typical value.

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there.

³ L70/B50

LED VALUE PAR16 80 / PAR16 50

LED reflector lamps PAR16



1

CRI
80

LED VALUE PAR16 80 / PAR16 50

Product Name	GTIN (EAN)	WΔW	W	lm	cd	K	Ra	Beam angle	Beam diameter	Beam diameter (mm)	Beam diameter (inches)	t(h)	Beam diameter (mm)	Beam diameter (inches)	No.
LED VALUE PAR16 50															
LV PAR16 50 36 4.5W/827 230V GU10	4058075588356	50	GU10	4.5	380	750	2,700	80	—	36°	54	50	15,000	10	1
LV PAR16 50 36 4.5W/840 230V GU10	4058075588370	50	GU10	4.5	400	750	4,000	80	—	36°	54	50	15,000	10	1
LV PAR16 50 36 4.5W/865 230V GU10	4058075588394	50	GU10	4.5	420	800	6,500	80	—	36°	54	50	15,000	10	1

¹Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values.

²LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there.

³L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage.

LED PERFORMANCE PAR16 80 / PAR16 50

Dimmable LED reflector lamps PAR16 high CRI



1



LED PERFORMANCE PAR16 80 / PAR16 50

Product Name	GTIN (EAN)	W _Δ W	≡	W	lm	cd	K	R _a	✓	°	mm	h	t(h)	h	h
LED PERFORMANCE PAR16 80															
LP PAR16 80 36 7.5W/927 230V GU10	4058075588059	80	GU10	7.5	630	850	2,700	90	✓	36°	52	50	25,000	10	1
LP PAR16 80 36 7.5W/930 230V GU10	4058075588073	80	GU10	7.5	630	850	3,000	90	✓	36°	52	50	25,000	10	1
LP PAR16 80 36 7.5W/940 230V GU10	4058075588097	80	GU10	7.5	650	950	4,000	90	✓	36°	52	50	25,000	10	1
LP PAR16 80 36 7.5W/965 230V GU10	4058075588110	80	GU10	7.5	650	950	6,500	90	✓	36°	52	50	25,000	10	1
LED PERFORMANCE PAR16 50															
LP PAR16 50 24 5.5W/927 230V GU10	4058075587359	50	GU10	5.5	380	1,200	2,700	90	✓	24°	52	51	25,000	10	1
LP PAR16 50 36 5.5W/927 230V GU10	4058075587373	50	GU10	5.5	380	750	2,700	90	✓	36°	52	51	25,000	10	1
LP PAR16 50 36 5.5W/930 230V GU10	4058075587137	50	GU10	5.5	380	350	3,000	90	✓	36°	52	51	25,000	10	1
LP PAR16 50 36 5.5W/940 230V GU10	4058075587199	50	GU10	5.5	400	350	4,000	90	✓	36°	52	51	25,000	10	1
LP PAR16 50 36 5.5W/965 230V GU10	4058075587335	50	GU10	5.5	400	350	6,500	90	✓	36°	52	51	25,000	10	1

¹Typical values. All the technical parameters apply to the entire lamp. In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values

²LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³L70B50 is the average operating life of the LED Lamp during which the luminous flux is greater than or equal to 70% of the initial luminous flux, for 50% of the population. The lifetime is estimated at room temperature (25°C), free air burning, base up burning position and at rated voltage