Product Specification Sheet





Contact:

(5)

	Mr.Kraisorn Faekhom
Tel:	+66(0)81-911-2537
Email:	kraisorn.f@minebea.co.th

Type: S3 Series Small Spotlight Beam Variable



Model No.	
Manufacturer	
Description	
Mounting Method	
Input voltage	
Input power	
Lamp	
Beam angle	
CRI	
Color temperature	
Total Luminous Flux	

LED Lifetime Finish Dimension Weight Adjustment MS-S3001TW-TH SALIOT Bluetooth Adjustable Small Spotlight Beam Variable CCT Tunable Direct through lighting busways JIS C8366, for indoor only 220 Vac 16W (Lighting), 19W (with Motors) Nichia LED (COB) 18~28° Beam angle(Manual) Ra90 2700K~5000K 554~828 Im

40,000 hours (70%) White As shown 0.8 Kg Dimming range 0, 1~100% Movement angle (deg.) PAN: 0~180° TILT: -90°~90°

Scene Special Function Control Remote Devices

Certification

16 Scenes Save&Load scene Bluetooth Mesh 4.1 (20m device to device) iOS 10 or later (iPhone, iPad and iPod touch) Android 7.0 or later TIS 1955-2551

> SALIOT App Free download in Available on the App Store Google play

Customer Approve Rev:A

The spec is subject to change without notice